



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
04.09.2002 Bulletin 2002/36

(51) Int Cl.7: **C10G 65/04**

(21) Application number: **02004489.7**

(22) Date of filing: **27.02.2002**

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

- **Fernandez, Nancy**
Colinas de Bello Monte, Caracas (VE)
- **Arteca, Rosa**
Av. Panteon San Jose, Caracas (VE)
- **Castillo, Carlos**
San Antonio (VE)

(30) Priority: **01.03.2001 US 797448**

(71) Applicant: **Intevp SA**
Caracas 1070 A (VE)

(74) Representative: **Hiebsch, Gerhard F., Dipl.-Ing.**
Hiebsch Peege Behrmann,
Patentanwälte,
Heinrich-Weber-Platz 1
78224 Singen (DE)

(72) Inventors:
• **Dassori, Carlos Gustavo**
Los Teques (VE)

(54) **Hydroprocessing process and a system for hydroprocessing**

(57) A process for hydroprocessing a hydrocarbon feedstock, includes the steps of providing a hydrocarbon feed having an initial characteristic; providing a first hydrogen-containing gas; feeding the hydrocarbon feed and the first hydrogen-containing gas cocurrently to a first hydroprocessing zone so as to provide a first hydrocarbon product; providing a plurality of additional hydroprocessing zones including a final zone and an upstream zone; feeding the first hydrocarbon product co-

currently with a recycled gas to the upstream zone so as to provide an intermediate hydrocarbon product; and feeding the intermediate hydrocarbon product cocurrently with a second hydrogen-containing gas to the final zone so as to provide a final hydrocarbon product having a final characteristic which is improved as compared to the initial characteristic.

EP 1 236 788 A2

Description

- [0001] The invention relates to a deep hydroprocessing process and, more particularly, to a process for advantageously removing substantial amounts of contaminant such as sulfur from hydrocarbon feedstocks.
- 5 [0002] A persistent problem in the art of petroleum refining is to reach acceptably low levels of sulfur content and other contaminants.
- [0003] A large portion of the world's hydrocarbon reserves contain sulfur, and removal of this sulfur is critical in order to provide acceptable fuels.
- 10 [0004] Government agencies are currently formulating new regulations which will require sulfur content in fuels to be substantially lower than current practice. It is expected that such regulations will require sulfur content of less than 15 wppm.
- [0005] A number of processes have been attempted for use in removing sulfur, one of which is hydrosulfurization, wherein a hydrogen flow is exposed to the feedstock in the presence of a suitable catalyst so that sulfur compounds react to produce a volatile product, hydrogen sulfide.
- 15 [0006] Such processes do provide substantial reduction in sulfur in the feed. However, existing facilities do not readily provide for reduction of sulfur content to desired levels. Known hydrosulfurization methods include cocurrent processes, wherein hydrogen and hydrocarbon feed are fed through a reactor or zone in the same direction, and countercurrent processes wherein hydrocarbon is fed in one direction and gas is fed in the other direction.
- 20 [0007] Known cocurrent processes do not provide acceptable levels of sulfur removal, and countercurrent processes typically experience difficulty in reactor flooding which occurs when the desired amount of gas flow to the reactor prevents flow of the hydrocarbon in the counter direction. Reduction of gas flow to address flooding reduces the effectiveness of countercurrent hydrosulfurization processes.
- [0008] Another potential problem with countercurrent processes is that adiabatic countercurrent processes may operate at temperatures much higher than adiabatic cocurrent processes, and this temperature is detrimental to hydrosulfurization and other catalysts used in the process.
- 25 [0009] Based upon the foregoing, it is clear that the need remains for an advantageous process for removal of sulfur to levels which will meet the expected regulations on hydrocarbons for use as fuel.
- [0010] It is therefore the primary object of the present invention to provide a process whereby sulfur content is advantageously reduced to less than or equal to about 10 wppm.
- 30 [0011] It is a further object of the present invention to provide a process which can be carried out without substantially increasing the equipment size and space occupied by same in current hydrosulfurization systems.
- [0012] It is still another object of the present invention to provide a hydrosulfurization system which accomplishes the aforesaid objectives.
- 35 [0013] The problems are solved by the teaching according to the independent claims. Particular developments are given in the dependent claims. Within the frame of the invention are all combinations of at least two of the descriptive elements and technical features disclosed in the claims and/or in the description.
- [0014] In accordance with the present invention, the foregoing objects and advantages have been readily attained.
- 40 [0015] In accordance with the invention, a process for removing sulfur from a hydrocarbon feedstock is provided, which process comprises the steps of providing a hydrocarbon feed having an initial characteristic; providing a first hydrogen containing gas; feeding said hydrocarbon feed and said first hydrogen gas cocurrently to a first hydroprocessing zone so as to provide a first hydrocarbon product; providing a plurality of additional hydroprocessing zones including a final zone and an upstream zone; feeding said first hydrocarbon product cocurrently with a recycled gas to said upstream zone so as to provide an intermediate hydrocarbon product; and feeding said intermediate hydrocarbon product cocurrently with a second hydrogen-containing gas to said final zone so as to provide a final hydrocarbon product having a final characteristic which is improved as compared to said initial characteristic.
- 45 [0016] Still further according to the invention, a system is provided for removing sulfur from a hydrocarbon feed, which system comprises a first hydroprocessing zone containing a hydroprocessing catalyst and having an inlet for cocurrently receiving a hydrocarbon feed and a first hydrogen-containing gas phase; a plurality of additional hydroprocessing zones each containing a hydroprocessing catalyst and including a final zone and an upstream zone, said upstream zone having an inlet for cocurrently receiving a hydrocarbon product from said first hydroprocessing zone and a recycled hydrogen-containing gas phase, said final zone having an inlet for cocurrently receiving a hydrocarbon product from said upstream hydroprocessing zone cocurrently with a second hydrogen-containing gas phase; and a separator for receiving a product from said final hydroprocessing zone and for separating said product into a hydrocarbon phase and said recycled hydrogen-containing gas phase.
- 50 [0017] The process and system of the present invention are particularly well suited for use in treating Diesel, gasoil and other distillate feedstocks to reduce sulfur and also for use in treating naphtha and like feedstocks as well.
- 55 [0018] Further advantages, characteristics and details of the invention are apparent from the following detailed description of preferred embodiments of the invention with reference to the attached drawing schematically illustrates a

multi-stage process in accordance with the present invention, wherein:

Figures 1 schematically illustrates a process and system in accordance with the present invention;

Figure 2 schematically illustrates an alternative embodiment of the process and system in accordance with the present invention;

Figure 3 illustrates the temperature of a process as a function of reactor length for cocurrent and countercurrent processes, as well as the process of the present invention;

Figure 4 illustrates the relationship of sulfur content and relative reactor volume for a process according to the present invention and a globally countercurrent process;

Figure 5 illustrates sulfur content as a function of relative reactor volume for processes according to the present invention with and without cold separator recycling;

Figure 6 illustrates the relationship between outlet sulfur content and relative reactor volume for a process according to the present invention, a pure cocurrent process, and a two-reactor inter-stage stripping process;

Figure 7 illustrates the relationship between outlet sulfur content and relative reactor volume for a process according to the present invention and for a process having different ratio of hydrogen distribution;

Figure 8 illustrates the relationship between outlet sulfur content and relative reactor volume for a process according to the present invention and for a process having an inverse distribution of catalyst between first and second stages;

Figure 9 illustrates the relationship between dimensionless reactor length and hydrogen partial pressure for a process according to the present invention and a pure cocurrent process;

Figure 10 illustrates the relationship between dimensionless reactor length and reactor temperature for a process according to the present invention as well as pure cocurrent and pure countercurrent processes; and

Figure 11 illustrates the relationship between outlet sulfur content and relative reactor volume for a process according to the present invention as well as a pure cocurrent and pure countercurrent process.

[0019] In accordance with the present invention, a hydroprocessing process and system are provided for removal of contaminants, especially sulfur from a hydrocarbon feed such as Diesel, gasoil, naphtha and the like. A particularly advantageous aspect of the present invention is hydrodesulfurization, and the following detailed description is given as to a hydrodesulfurization process.

[0020] The process and system of the present invention advantageously allow for reduction of sulfur content to less than or equal to about 10 wppm, which is expected to satisfy regulations currently proposed by various Government agencies, without requiring substantial expense for new equipment, additional reactors, and the like.

[0021] In accordance with the present invention, a process is provided which combines a single cocurrently operated hydrodesulfurization reactor with a second stage including a plurality of hydrodesulfurization reactors to obtain a desired result. As will be further discussed below, the second stage includes a plurality of additional hydrodesulfurization reactors or zones and is operated in a globally countercurrent, yet locally cocurrent, mode. This means that when considered on the basis of the reactors overall, the hydrocarbon and hydrogen-containing gas are fed in opposite directions. However, each reactor or zone is coupled so as to flow the hydrocarbon and hydrogen-containing gas in a cocurrent direction within that reactor, thereby providing the benefits of globally countercurrent flow, while avoiding the flooding problems which might be experienced with local countercurrent flow through a reactor or zone.

[0022] The reactors within the second stage are arranged such that the hydrocarbon feedstock travels from a first reactor to a last or final reactor, and the hydrogen gas phase travels from the last reactor to the first reactor. In the following detailed description, the group of reactors that are utilized in the second zone are referred to as including a final reactor, from which the finally treated hydrocarbon exits, and upstream reactors which are upstream of the final reactor when taken in connection with the flow of hydrocarbon. Thus, in Figure 1, reactor 28 is upstream from reactor 30 when considered in light of the direction of hydrocarbon flow, and in Figure 2, reactor 52 is upstream of reactor 54, and reactor 50 is upstream of both reactors 52 and 54, also when considered in connection with the direction of hydrocarbon flow. Thus, as used herein, an upstream reactor is a reactor which is upstream as it relates to hydrocarbon flow.

[0023] In accordance with the present invention, the hydrodesulfurization steps to be carried out are accomplished by contacting or mixing the hydrocarbon feed containing sulfur with a hydrogen gas-containing phase in the presence of a hydrodesulfurization catalyst and at hydrodesulfurization conditions whereby sulfur species within the hydrocarbon convert to hydrogen sulfide gas which remains with the hydrogen gas phase upon separation of liquid and gas phases. Suitable catalyst for use in hydrodesulfurization processes are well known to a person of ordinary skill in the art, and selection of the particular catalyst forms no part of the present invention.

[0024] In connection with the gas phase, suitable gas contains hydrogen as desired for the hydroprocessing reaction. This gas may be substantially pure hydrogen or may contain other gases, so long as the desired hydrogen is present for the desired reaction. Thus, as used herein, hydrogen-containing gas includes substantially pure hydrogen gas and

other hydrogen-containing streams.

[0025] Turning now to Figure 1, a hydrodesulfurization process in accordance with the present invention is schematically illustrated.

[0026] As shown, the process is carried out in a first stage 10 and a second stage 12, so as to provide a final hydrocarbon product having acceptably low content of sulfur.

[0027] As shown, first stage 10 is carried out utilizing a first reactor 14 to which is fed a hydrocarbon feed 16 containing an initial amount of sulfur. Feed 16 is combined with a hydrogen-containing gas 18 and fed cocurrently through reactor 14 such that cocurrent flow of hydrocarbon feed 16 and gas 18 in the presence of hydrodesulfurization catalyst and conditions converts sulfur species within the hydrocarbon into hydrogen sulfide within the product 20 of reactor 14. Product 20 is fed to a liquid gas separator 22 where a predominately hydrogen and hydrogen sulfide containing gas phase 24 is separated from an intermediate product 26. Intermediate product 26 has a reduced sulfur content as compared to hydrocarbon feed 16, and is fed to second stage 12 in accordance with the present invention for further treatment to reduce sulfur content.

[0028] As shown, second stage 12 preferably includes a plurality of additional reactors 28, 30, which are connected in series for treating intermediate product 26 as will be further discussed below. As shown, reactor 28 preferably receives intermediate hydrocarbon feed 26 which is mixed with a recycled hydrogen gas 31 and fed cocurrently through reactor 28. Product 32 from reactor 28 is then fed to a liquid gas separator 34 for separation of a predominately hydrogen and hydrogen sulfide containing gas phase 36 and a further treated liquid hydrocarbon product 38 having a sulfur content still further reduced as compared to intermediate hydrocarbon feed 26. Hydrocarbon feed 38 is then fed to reactor 30, combined with an additional hydrogen feed 40 and fed cocurrently with hydrogen feed 40 through reactor 30 to accomplish still further hydrodesulfurization and produce a final product 42 which is fed to a separator 44 for separation of a gas phase 46 containing hydrogen and hydrogen sulfide as major components, and a final liquid hydrocarbon product 48 having substantially reduced sulfur content.

[0029] In accordance with the present invention, gas phase 46 is recycled for use as recycled gas 31 such that gas flowing through the reactors of second stage 12 is globally countercurrent to the flow of hydrocarbon through same. Considering the flow of hydrocarbon from reactor 28 to reactor 30, it is readily apparent that reactor 28 is an upstream reactor and reactor 30 is a final reactor of second stage 12. It should of course be appreciated that additional upstream reactors could be included in second stage 12 if desired, and that second stage 12 preferably includes at least two reactors 28, 30 as shown in the drawings. However, it is a particular advantage of the present invention that excellent results are obtained utilizing the first and second stages as described above with a like number of reactors as are currently used in conventional processes, thereby avoiding the need for additional equipment and space.

[0030] It should also be appreciated that although Figure 1 shows reactors 14, 28 and 30 as separate and discrete reactors, the process of the present invention could likewise be carried out by defining different zones within a collectively arranged reactor, so long as the zones are operated with flow of feed and gas as described above for the first and second stages, with local cocurrent flow through each zone of both stages and globally countercurrent flow through the at least two zones of second stage 12.

[0031] Turning now to Figure 2, a further embodiment of the present invention is illustrated.

[0032] As shown, first stage 10 includes a single reactor 14 in similar fashion to the embodiment of Figure 1.

[0033] Second stage 12 in this embodiment includes reactors 50, 52, and 54, and each reactor is operated in a similar fashion to the second stage reactors of the embodiment of Figure 1 so as to provide a single cocurrent stage in first stage 10 and a globally countercurrent, locally cocurrent process in second stage 12. Thus, feed 56 and fresh hydrogen-containing gas 58 are fed cocurrently to reactor 14 so as to produce product 60 which is fed to separator 62 to produce an intermediate liquid hydrocarbon product 64 and gas phase 66 containing hydrogen and hydrogen sulfide as major components. Intermediate hydrocarbon product 64 is then fed to second stage 12, where it is mixed with recycled gas 68 and fed cocurrently through reactor 50 to produce product 70 which is fed to separator 72. Separator 72 separates a further intermediate liquid hydrocarbon product 74 and a gas phase 76 containing hydrogen and hydrogen sulfide as major components.

[0034] Intermediate hydrocarbon product 74 is then combined with recycled hydrogen 78 and fed to reactor 52, cocurrently, so as to produce a further intermediate product 80 which is fed to separator 82 for separation of a further liquid hydrocarbon feed 84 and a gas phase 86 containing hydrogen and hydrogen sulfide as major components which are advantageously fed to upstream reactor 50 as recycled gas 68'. Hydrocarbon product 84 is then advantageously combined with a fresh hydrogen feed 88 and fed to last reactor 54, cocurrently, for further hydrodesulfurization so as to provide product 90 which is fed to separator 92 for separation of hydrocarbon liquid phase 94 and gas phase 96 containing hydrogen and hydrogen sulfide as major components. Advantageously, gas phase 96 is fed to upstream reactor 52 and recycled as recycled gas 78 for use in that process, while liquid phase 94 can be treated as a final product, or alternatively can be treated further as discussed below.

[0035] In accordance with the present invention, a hydrodesulfurization catalyst is present in each reactor, and each successive hydrocarbon product has a sulfur content reduced as compared to the upstream hydrocarbon feed. Further,

the final hydrocarbon product has a final sulfur content which is substantially reduced as compared to the initial feed, and which is advantageously less than or equal to about 10 wppm so as to be acceptable under new regulations from various Government agencies.

5 **[0036]** Further, it should be readily apparent that second stage 12 of the embodiment of Figure 2 is globally countercurrent, as with the embodiment of Figure 1. Specifically, hydrocarbon is fed from reactor 50 to reactor 52 and finally to final reactor 54, while gas phase is fed from reactor 54 to reactor 52 and finally to reactor 50. This provides for the advantages of a globally countercurrent process, while avoiding flooding problems which could occur with locally countercurrent processes.

10 **[0037]** Still referring to Figure 2, it may be desirable to feed gas phases 66 and 76 to a low temperature separator 98 which operates to remove volatile hydrocarbon product 100, which can be recycled back as additional feed 56 for further treatment in accordance with the process of the present invention, with a purge stream 101 also as shown. Low temperature separator 98 also separates a gas phase 102 which can advantageously be mixed with final product 94 and fed to a final separator 104 so as to obtain a further treated final hydrocarbon product 106 and a final gas phase 108 containing hydrogen and the bulk of removed sulfur. Product 106 can be further treated for enhancing various
15 desired qualities as a hydrocarbon fuel, or can be utilized as hydrocarbon fuel without further treatment, since the sulfur content has been advantageously reduced to acceptable levels.

[0038] Final gas phase 108 can advantageously be fed to a stripper or other suitable unit for removal of hydrogen sulfide to provide additional fresh hydrogen for use as hydrogen feeds 58 or 88 in accordance with the process of the present invention.

20 **[0039]** It should readily be appreciated that Figures 1 and 2 further illustrate a system for carrying out the process in accordance with the present invention.

[0040] Typical feed for the process of the present invention includes Diesel, gasoil and naphtha feeds and the like. Such feed will have an unacceptably high sulfur content, typically greater than or equal to about 10 wppm. The feed and total hydrogen are preferably fed to the system at a global ratio of gas to feed of between about 500 scfb and
25 about 4000 scfb (std. cubic feet/barrel). Further, each reactor may suitably be operated at a temperature of between about 300°C and about 420°C, and a pressure of between about 400 psi and about 1500 psi.

[0041] In accordance with the present invention, it should readily be appreciated that catalyst volume and gas streams are distributed between the first zone and the second zone. In accordance with the present invention, the most suitable distribution of gas catalyst is determined utilizing an optimization process. It is preferred, however, that the total catalyst
30 volume be distributed between the first zone and the second zone with between about 20 and about 80% volume of the catalyst in the first zone and between about 80 and about 20% volume of the catalyst in the second zone. Further, as discussed above, the total hydrogen is fed to the system of the present invention with one portion to the first zone and the other portion to the final reactor of the second zone. It is preferred that between about 20 and 70% volume of the total hydrogen for the reaction be fed to the first zone, with the balance being fed to the final reactor of the second
35 zone.

[0042] It should be noted that as with all hydrodesulfurization processes, the hydrodesulfurization catalyst will gradually lose effectiveness over time, and this can be advantageously countered in the process of the present invention by increasing gas flow rate if desired. This is possible with the process of the present invention because locally cocurrent flow is utilized, thereby preventing difficulties associated with flooding and the like in locally countercurrent processes.

40 **[0043]** It should also be appreciated that the process of the present invention can advantageously be used to reduce sulfur content of naphtha feed. In such processes, condensers would advantageously be positioned after each reactor, rather than separators, so as to condense the reduced sulfur naphtha hydrocarbon product while maintaining the gas phase containing hydrogen and hydrogen sulfide as major components. In all other respects, this embodiment of the present invention will function in the same manner as that described in connection with Figures 1 and 2.

45 **[0044]** Turning now to Figure 3, and as set forth above, the process of the present invention combining in a hybrid fashion a first stage purely cocurrent reaction and a second stage which is globally countercurrent and locally cocurrent advantageously provides for operation of the reactors at reduced temperatures as compared to countercurrent processes. Figure 3 illustrates temperature as a function of dimensionless reactor length for a typical cocurrent process, for a countercurrent process, and for a hybrid process in accordance with the present invention. As shown, the temperature in the countercurrent process is substantially higher than the hybrid process of the present invention, with the
50 result that the catalyst of the hybrid process of the present invention is subjected to less severe and damaging conditions.

[0045] In accordance with the present invention, improved results are obtained using the same amounts of catalyst and hydrogen as a conventional countercurrent or cocurrent process. In accordance with the present invention, however, the hydrogen feed is divided into a first portion fed to the first stage and a second portion fed to the second stage, and the catalyst volume is also divided between the first stage and second stage, which are operated as discussed
55 above, so as to provide improved hydrodesulfurization as desired.

[0046] As set forth above, one particularly advantageous hydrocarbon feed with which the process of the present

invention can be used is a gasoil feed. In a typical application, a reactor can be provided having a reactor diameter of about 3.8 meters, a reactor length of about 20 meters, and a cocurrent feed of hydrogen to gasoil at a ratio of hydrogen gas to gasoil of about $270 \text{ Nm}^3/\text{m}^3$, a temperature of about 340°C , a pressure of about 750 psi and a liquid hourly space velocity (LHSV) through the reactor of about 0.4 h^{-1} .

[0047] The gasoil may suitably be a vacuum gasoil (VGO) an example of which is described in Table 1 below.

TABLE 1

API gravity (60°C)	17.3
Molecular weight (g/mol)	418
Sulfur content, %wt	2
Simulated Distillation ($^\circ\text{C}$)	
IBP/5, %v	236/366
10/20, %v	392/413
30/50, %v	431/454
70/80, %v	484/501
90/95, %v	522/539
FBP	582

[0048] For such a feedstock, easy-to-react (ETR) sulfur compounds would be, for example, 1-butylphenanthrothiophene. When contacted with hydrogen at suitable conditions, this sulfur compound reacts with the hydrogen to form hydrogen sulfide and butylphenantrene. A typical difficult-to-react (DTR) sulfur compound in such a feed is heptyldibenzothiophene. When contacted with hydrogen gas under suitable conditions, this reacts to form hydrogen sulfide and heptylbiphenyl.

[0049] It should of course be appreciated that although the above description is given in terms of hydrodesulfurization processes, the hybrid process of the present invention is readily applicable to other hydroprocessing systems, and can advantageously be used to improve hydroprocessing efficiency in various different processes while reducing problems routinely encountered in the art.

Example 1

[0050] A VGO feed as described in Table 1 was used with a series of different hydrodesulfurization processes, and conversion of sulfur compounds and sulfur in the final product were modeled for each case. The results are set forth in Table 2 below.

TABLE 2

CASE	VGO Flow rate (BBL/D)	Gas Flow rate Nm ³ /h	CONVERSION %		%S (wt.)	REACTOR VOLUME LHSV	
			C ₄ FT(ETR)	C ₆ DBT(DTR)		(m ³)	(h ⁻¹)
CASE 1	2000	35162	94.14	75.74	OUTLET 0.19	322 L=28 m	0.4
CASE 2	20000	35162	98.79	98.37	0.0256	322 R1=R2=...=Rn L=28 m n=20	
CASE 3	20000	35162	99.3	95.9	0.0271	322 L=28 R1=R2=R3	0.4
CASE 4	20000	35162	98.99	90.259	0.053	322 L=28 R1=R2	0.4
CASE 5	20000	First 26371.5 Last 8790.5	99.8	97	0.016	322 L=28 m R=60%L R2=R3=20%L	0.4
CASE 6	20000	First 26371.5 Last 8790.5	99.93	99.5	0.00317	483	0.27
CASE 7	20000	35162	99.9	99.2	0.00313	L=133m 1508	0.09
CASE 8	20000	First 26371.5 Last 8790.5	99.9	99.7	0.0021	962	0.14
CASE 9	20000	35162	99.9	96.4	0.0162	962 R1,L=28m, D=3.8, R2,L=20.86m, D=4.42m, R2,L=20.86m, D=4.42m	0.14

TABLE 2 (continued)

CASE	VGO Flow rate (BBL/D)	Gas Flow rate Nm ³ /h	CONVERSION %		%S (wt.)	REACTOR VOLUME LHSV	
			C ₄ FT(ETR)	C ₆ DBT(DTR)	OUTLET	(m ³)	(h ⁻¹)
CASE 10	20000	35162	99.9	99.5	0.00312	962 R1, L=28m, D=3.8, R2, L=20.86m, D=4.42m, R2, L=20.86m, D=4.42m	0.14

where D = diameter;

R = length of reactor; and

L = total length.

[0051] In Table 2, cases 5, 6 and 8 are carried out in accordance with the process of the present invention. For comparison purposes, cases 1 and 7 were carried out utilizing a single reactor through which were fed, cocurrently, VGO and hydrogen.

[0052] Case 2 was carried out utilizing 20 reactors arranged for globally countercurrent and locally cocurrent flow as illustrated in the second stage portion of Figure 1.

[0053] Cases 3 and 10 were also carried out utilizing globally countercurrent and locally cocurrent flow as in stage 2 alone of Figure 1.

[0054] Case 4 was carried out utilizing two reactors with an intermediate hydrogen sulfide separation stage, and case 9 was carried out utilizing pure cocurrent flow, globally and locally, through three reactors.

[0055] At the flow rates shown, results were modeled and are set forth in Table 2.

[0056] Cases 1-5 were all carried out utilizing reactors having a volume of 322m³, and at the same VGO and gas flow rates. As shown, case 5, utilizing the two stage hybrid process of the present invention, provided the best results in terms of conversion of sulfur compounds and sulfur remaining in the final product. Further, this substantial improvement in hydrodesulfurization was obtained utilizing the same reactor volume, and could be incorporated into an existing facility utilizing any configuration of cases 1-4 without substantially increasing the area occupied by the reactors.

[0057] Case 6 in Table 2 shows that by reasonable increase in reactor volume, still further advantageous results can be obtained in accordance with the process of the present invention, and final sulfur content would satisfy the strictest of expected regulations in connection with maximum sulfur content, and this is accomplished through only a small increase in reactor volume.

[0058] Case 7 of Table 2 shows that in order to accomplish similar sulfur content results to case 6, a single reactor operated in a single cocurrent conventional process would require almost 4 times the reactor volume as case 6 in accordance with the process of the present invention.

[0059] Cases 8, 9 and 10 are modeled for a reactor having a volume of 962m³, and the hybrid process of the present invention (Case 8) clearly shows the best results as compared to Cases 9 and 10.

[0060] In accordance with the foregoing, it should be readily apparent that the process of the present invention is advantageous over numerous alternative configurations.

Example 2

[0061] In this example, a Diesel feed was treated utilizing several different process schemes and, sulfur compound conversion and sulfur content in the final product were calculated. The Diesel for this example had characteristics as follows:

Diesel	
API = 27	
MW = 213	
Sulfur = 1.10%wt	
Simulated Distillation(°C)	
IBP-5	177/209
10-20	226/250
30-40	268/281
50-60	294/308
70-80	323/339
90-95	357/371
FBP	399

[0062] Table 3 below sets forth the process conditions and results of each case.

TABLE 3

CASE	Diesel Flowrate (BBL/D)	Gas Flow rate Nm ³ /h	CONVERSION		%S (wt) OUTLET	REACTOR VOLUME (m ³)	LHSV (h ⁻¹)
			EDBT(ETR)	DMDBT(OTR)			
CASE 1	35000	24039	96.5	81.6	0.072	370 L=35m	0.63
CASE 2	35000	24039	93.72	93.44	0.07	370 R1=R2...=Rn L=35m n=20	0.63
CASE 3	35000	First 18029 Last 6010	99.28	96.8	0.0135	370 L=35m R1=60%L R2=R3=20%L	0.63
CASE 4	35000	24039	96.52	81.6	0.072	370 L=35m	0.63
CASE 5	72000	First 37097 Last 12366	96.08	82.53	0.074	370 L=35m	1.3

[0063] Case 1 of Table 3 was carried out by cocurrently feeding a Diesel and hydrogen feed through a single reactor having the shown length and volume.

[0064] Case 2 was carried out feeding Diesel and hydrogen globally countercurrently, and locally cocurrently, through 20 reactors having the same total length and volume as in Case 1.

5 [0065] Case 3 was carried out in accordance with the process of the present invention, utilizing a first single reactor stage and a second stage having two additional reactors operated globally countercurrently and locally cocurrently, with the gas flow rate split as illustrated in Table 3. As shown, the process in accordance with the present invention (Case 3) clearly performs better than Cases 1 and 2 for sulfur compound conversion and final sulfur content while utilizing a reactor system having the same volume. Case 4 is the same as Case 1 and is presented for comparison to
10 Case 5 wherein a process in accordance with the present invention was operated to obtain the same sulfur content from the same reactor volume as the conventional scheme for process so as to illustrate the potential increase in reactor capacity by utilizing the process of the present invention. By adjusting the process to obtain substantially the same final sulfur content, the same reactor volume is able to provide more than double the Diesel treatment capacity as compared to the conventional process.

15 Example 3

[0066] In this example, a process in accordance with the present invention was compared to a globally countercurrent and locally cocurrent process. Each process was utilized having 4 reactors with the same catalyst, a Diesel feed, and operating at a temperature of 320°C, a pressure of 478 psi, and a ratio of hydrogen to feed of 104 Nm³/m³. Figure
20 4 shows the results in terms of sulfur content in the final product as a function of relative reactor volume. As shown, the hybrid process of the present invention provides substantially improved results.

25 Example 4

[0067] In this example, two processes were evaluated. The first was a process in accordance with a preferred embodiment of the present invention wherein cold separators were positioned after each reactor for recycling condensed vapors. For the same reactors, feed, temperature, pressure and hydrogen/feed ratio, Figure 5 illustrates the relation between final sulfur content and relative reactor volume for a process in accordance with the present invention using
30 cold separators (curve 1), as compared to a process in accordance with the present invention without cold separators (curve 2). As shown, the use of cold separators provides additional benefit in reducing the final sulfur content by allowing sufficient hydrodesulfurization of all sulfur species, even those that go into the gas phase.

35 Example 5

[0068] In this example, a comparison is presented showing final sulfur content as a function of relative reactor volume for a conventional cocurrent process, for a two stage process using an inter-stage stripper, and for a process in accordance with the present invention. The feedstock, temperature, pressure and hydrogen/feed ratio were maintained the same, and the results are illustrated in Figure 6. As shown, the process of the present invention provides better
40 results in terms of final sulfur content than either of the other two processes.

Example 6

[0069] In this example, the importance of the proper distribution of hydrogen feed to the first stage and second stage in the process of the present invention is demonstrated.

[0070] An example is provided to evaluate hydrogen distribution using a hydrogen feed of 50% to the first stage, and a hydrogen feed of 50% to the last reactor of the second stage. This was compared to a case run using the same equipment and total gas volume, with an 80% feed to the first stage and a 20% feed to the second stage.

50 [0071] Figure 7 shows the results in terms of outlet sulfur content as a function of relative reactor volume for the process in accordance with the present invention and for the 80/20 hydrogen distribution. As shown, in this instance the 50/50 distribution provides better results.

Example 7

55 [0072] In this example, the importance of the distribution of catalyst between the first and second stages is illustrated. A four reactor setup in accordance with the present invention, with one reactor in the first stage and three reactors operated globally countercurrent and locally cocurrent in the second stage was used. In one evaluation according to the present invention, 30% of the total catalyst volume was positioned in the first reactor, and 70% of the total catalyst

volume was divided equally among the three reactors of the second stage.

[0073] For comparison, the same system was operated providing 70% of total catalyst volume in the first stage, and 30% of catalyst volume in the second stage.

[0074] Figure 8 shows the results in terms of sulfur content as a function of relative reactor volume for the 30/70 process of the present invention as compared to the 70/30 process. As shown, the process of the present invention provides significantly better results.

Example 8

[0075] In this example, the hydrogen partial pressure was evaluated, as a function of dimensionless reactor length, for a process in accordance with the present invention and for a pure cocurrent process.

[0076] Figure 9 shows the results of this evaluation, and shows that the process in accordance with the present invention provides for significantly increased hydrogen partial pressure at the end of the reactor, which is desirable. This provides for higher hydrogen partial pressures so as to provide reacting conditions that are most suited for reacting the most difficult-to-react sulfur species, thereby providing conditions for enhanced hydrodesulfurization, particularly as compared to the pure cocurrent case.

Example 9

[0077] In this example, a comparison is provided for temperature as a function of dimensionless reactor length for a pure cocurrent process, a pure countercurrent process and the hybrid process of the present invention.

[0078] For the same reactor volume, catalyst volume and hydrogen/feed ratio, Figure 10 shows the resulting temperatures over dimensionless reactor length. As shown, the countercurrent process has the highest temperatures. Further, the hybrid process of the present invention is quite similar in temperature profile to that of the pure cocurrent process, with the exception that there is a slight decrease in temperature toward the reactor outlet.

[0079] This is beneficial since the higher temperatures, particularly those experienced with countercurrent process, serve to accelerate catalyst deactivation.

Example 10

[0080] In this example, the sulfur content as a function of relative reactor volume was evaluated for a process in accordance with the present invention, a pure cocurrent process and a globally countercurrent process for a VGO feedstock with a process using a four reactor train, with the same feedstock, and a temperature of 340°C, a pressure of 760 psi and a hydrogen/feed ratio of 273 Nm³/m³. Figure 11 shows the results of this evaluation, and shows that the process of the present invention performs substantially better than the pure cocurrent and pure countercurrent processes, especially in the range of resulting sulfur content which is less than 50 wppm.

[0081] In accordance with the foregoing, it should be readily apparent that the process and system of the present invention provide for substantial improvement in hydrodesulfurization processes which can be utilized to reduce sulfur content in hydrocarbon feeds with reactor volume substantially the same as conventional ones, or to substantially increase reactor capacity from the same reactor volume at substantially the same sulfur content as can be accomplished utilizing conventional processes.

[0082] It is to be understood that the invention is not limited to the illustrations described and shown herein, which are deemed to be merely illustrative of the best modes of carrying out the invention, and which are susceptible of modification of form, size, arrangement of parts and details of operation. The invention rather is intended to encompass all such modifications which are within its spirit and scope as defined by the claims.

Claims

1. A process for hydroprocessing a hydrocarbon feedstock, comprising the steps of:
 - providing a hydrocarbon feed having an initial characteristic;
 - providing a first hydrogen-containing gas;
 - feeding said hydrocarbon feed and said first hydrogen-containing gas cocurrently to a first hydroprocessing zone so as to provide a first hydrocarbon product;
 - providing a plurality of additional hydroprocessing zones including a final zone and an upstream zone;
 - feeding said first hydrocarbon product cocurrently with a recycled gas to said upstream zone so as to provide an intermediate hydrocarbon product; and

feeding said intermediate hydrocarbon product cocurrently with a second hydrogen-containing gas to said final zone so as to provide a final hydrocarbon product having a final characteristic which is improved as compared to said initial characteristic.

- 5 2. The process according to claim 1, wherein said initial characteristic is an initial sulfur content and said final characteristic is a final sulfur content which is less than said initial sulfur content.
3. The process according to claim 2, wherein said final sulfur content is less than or equal to about 10 wppm based upon weight of said final product.
- 10 4. The process according to claim 1, wherein said first hydroprocessing zone is a first hydrodesulfurization zone.
5. The process according to claim 1 or 4, wherein said additional hydroprocessing zones comprise additional hydrodesulfurization zones.
- 15 6. The process according to one of the claims 1 to 5, wherein said first hydrodesulfurization zone and said upstream hydrodesulfurization zone each produce a gas phase containing hydrogen sulfide hydrogen and volatile hydrocarbon fractions and further comprising feeding said gas phase to a low temperature separator for separating a liquid phase containing said volatile hydrocarbon fractions and a gas phase containing said hydrogen sulfide and hydrogen, and combining said volatile hydrocarbon fractions with said hydrocarbon feed.
- 20 7. The process according to one of the claims 1 to 6, wherein said final zone also produces a hydrogen-containing gas phase, and further comprising feeding said hydrogen-containing gas phase to said upstream zone as said recycled gas.
- 25 8. The process according to one of the claims 1 to 7, wherein said first hydrogen-containing gas and said second hydrogen-containing gas are separate quantities of fresh hydrogen-containing gas, and wherein said recycled gas contains contaminant removed from said intermediate hydrocarbon product.
- 30 9. The process according to one of the claims 1 to 8, wherein each of said first hydroprocessing zone and said plurality of additional zones contains a hydroprocessing catalyst.
10. The process according to one of the claims 1 to 9, wherein said hydrocarbon feed is a Diesel feed or wherein said hydrocarbon feed is a gasoil feed.
- 35 11. The process according to one of the claims 1 to 9, wherein said hydrocarbon feed is a naphtha feed, and further comprising feeding a product of said first hydroprocessing zone and said plurality of additional hydroprocessing zones to a condenser for providing liquid phase naphtha and gas phase hydrogen and hydrogen sulfide.
- 40 12. A system for hydroprocessing a hydrocarbon feed, comprising:
 - a first hydroprocessing zone containing a hydroprocessing catalyst and having an inlet for cocurrently receiving a hydrocarbon feed and a first hydrogen-containing gas phase;
 - 45 a plurality of additional hydroprocessing zones each containing a hydroprocessing catalyst and including a final zone and an upstream zone, said upstream zone having an inlet for cocurrently receiving a hydrocarbon product from said first hydroprocessing zone and a recycled hydrogen-containing gas phase, said final zone having an inlet for cocurrently receiving a hydrocarbon product from said upstream hydroprocessing zone cocurrently with a second hydrogen-containing gas phase; and
 - 50 a separator for receiving a product from said final hydroprocessing zone and for separating said product into a hydrocarbon phase and said recycled hydrogen-containing gas phase.
13. The system of claim 12, wherein said first hydroprocessing zone is a hydrodesulfurization zone containing a hydrodesulfurization catalyst.
- 55 14. The system of claim 12 or 13, wherein said additional hydroprocessing zones comprise at least one additional hydrodesulfurization zone containing a hydrodesulfurization catalyst.
15. The system of claim 12 or 14, wherein each of said first hydroprocessing zone and said additional hydroprocessing

zones is a hydrodesulfurization zone containing a hydrodesulfurization catalyst.

5

10

15

20

25

30

35

40

45

50

55




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11

THIS PAGE BLANK (USPTO)

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 236 788 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
15.01.2003 Bulletin 2003/03

(51) Int Cl.7: **C10G 65/04**

(43) Date of publication A2:
04.09.2002 Bulletin 2002/36

(21) Application number: **02004489.7**

(22) Date of filing: **27.02.2002**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR**
Designated Extension States:
AL LT LV MK RO SI

• **Fernandez, Nancy**
Colinas de Bello Monte, Caracas (VE)
• **Arteca, Rosa**
Av. Panteon San Jose, Caracas (VE)
• **Castillo, Carlos**
San Antonio (VE)

(30) Priority: **01.03.2001 US 797448**

(71) Applicant: **Intevp SA**
Caracas 1070 A (VE)

(74) Representative: **Hiebsch, Gerhard F., Dipl.-Ing.**
Hiebsch Peege Behrmann,
Patentanwälte,
Heinrich-Weber-Platz 1
78224 Singen (DE)

(72) Inventors:
• **Dassori, Carlos Gustavo**
Los Teques (VE)

(54) Hydroprocessing process and a system for hydroprocessing

(57) A process for hydroprocessing a hydrocarbon feedstock, includes the steps of providing a hydrocarbon feed having an initial characteristic; providing a first hydrogen-containing gas; feeding the hydrocarbon feed and the first hydrogen-containing gas cocurrently to a first hydroprocessing zone so as to provide a first hydrocarbon product; providing a plurality of additional hydroprocessing zones including a final zone and an upstream zone; feeding the first hydrocarbon product co-

currently with a recycled gas to the upstream zone so as to provide an intermediate hydrocarbon product; and feeding the intermediate hydrocarbon product cocurrently with a second hydrogen-containing gas to the final zone so as to provide a final hydrocarbon product having a final characteristic which is improved as compared to the initial characteristic.

EP 1 236 788 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 02 00 4489

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 5 292 428 A (HARRISON GEORGE E ET AL) 8 March 1994 (1994-03-08) * column 7, line 34 - line 45 * * column 9, line 34 - line 40 * * column 11, line 14 - line 30 * * column 12, line 39 - column 15, line 28; claims 1,7,9,10; figures 1,2 *	1-7,9-15	C10G65/04
X	US 5 720 872 A (GUPTA RAMESH) 24 February 1998 (1998-02-24) * column 3, line 15 - column 5, line 60 * * column 6, line 66 - column 7, line 8; claims 1,3; figure 2 *	1-5,7-15	
X	US 6 017 442 A (DRAKE CHARLES A ET AL) 25 January 2000 (2000-01-25) * column 6, line 18 - column 7, line 13; claims 1,6,8; figure 2 *	1-5,7, 9-15	
X	US 5 779 992 A (HIGASHI HIDEHIRO) 14 July 1998 (1998-07-14) * column 4, line 16 - line 23; claims 1,6; figure 5 *	1,2,4,5, 7,9,10, 12-15	TECHNICAL FIELDS SEARCHED (Int.Cl.7) C10G
X	US 4 431 525 A (HENSLEY JR ALBERT L ET AL) 14 February 1984 (1984-02-14) * claim 1; figure 1 *	1,2,4,5, 7,9, 12-15	
X	US 3 809 664 A (FANTA G ET AL) 7 May 1974 (1974-05-07) * the whole document *	1,2,5,9	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 20 November 2002	Examiner Deurinck, P
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same category A: technological background O: non-written disclosure P: intermediate document</p> <p>F: theory or principle underlying the invention E: earlier patent document, but published on, or after the filing date D: document cited in the application L: document cited for other reasons &: member of the same patent family, corresponding document</p>			

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 02 00 4489

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

20-11-2002

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5292428 A	08-03-1994	AT 109198 T	15-08-1994
		DE 69011112 D1	01-09-1994
		DE 69011112 T2	10-11-1994
		DK 474664 T3	27-03-1995
		EP 0474664 A1	18-03-1992
		ES 2061036 T3	01-12-1994
		WO 9013617 A1	15-11-1990
		WO 9208772 A1	29-05-1992
		JP 2895621 B2	24-05-1999
		JP 4505179 T	10-09-1992
		NO 914379 A	06-01-1992
US 5720872 A	24-02-1998	AU 5715298 A	31-07-1998
		EP 0954557 A1	10-11-1999
		JP 2001507740 T	12-06-2001
		NO 993177 A	25-06-1999
		WO 9829520 A1	09-07-1998
US 6017442 A	25-01-2000	NONE	
US 5779992 A	14-07-1998	JP 7053967 A	28-02-1995
		JP 10060456 A	03-03-1998
		DE 69427220 D1	21-06-2001
		DE 69427220 T2	25-04-2002
		EP 0665282 A1	02-08-1995
		WO 9505434 A1	23-02-1995
		KR 141884 B1	15-06-1998
		US 5591325 A	07-01-1997
US 4431525 A	14-02-1984	NONE	
US 3809664 A	07-05-1974	NONE	

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

THIS PAGE BLANK (USPTO)